

Insul-Quilt has been manufactured in Los Angeles, California exclusively for the film studios of Hollywood and beyond since the 1960's. Our client list is a "who's who" of the film industry, and we're privileged to be associated with a company that has such a pioneering history and is the first choice film studio liner worldwide.



PRODUCT SPECIFICATION

Manufactured using two 25mm layers of 24kgs/m³ density glass fibre, a foil coated backing paper is applied as well as an open weave glass cloth face layer. When stitched together, a duvet like structure is formed. Supplied either in black or white as standard, customised colours are available at an extra cost. A BS476 Class 0 Fire Certification has been achieved.

TECHNICAL DATA

SOUND TEST DATA - PER ASTM 795 TYPE A MOUNTING

Noise Reduction Coefficient Type A Test for Insul-Quilt

125	250	500	1000	2000	4000	NRC
24.0	66.3	62.5	55.7	53	51.5	
0.38	1.04	0.98	0.87	0.83	0.80	0.95

Sound absorption (Sabins)

Noise Reduction Coefficient 95%

INSTALLATION

Insul-Quilt can be installed in a number of ways. Where the substrate is plasterboard, drywall screws and washers can be used. Where the substrate is more robust, a nail gun can be used. Please refer to the images below showing examples of installation.

